

**5** OUTBOARD  
YEARS  
warranty

FOR LEISURE USE ONLY  
Subject to terms and conditions  
see your Dealer for more  
information

# OUTBOARD MOTORS



**SELVA**™



**QuattroT**  
**XSR**

**QuattroT**

**f** Selva  
Marine





# OUTBOARD MOTORS

45 powerful companions of navigation



**45 models • 2 range**

**Power from 2.5 Hp to 2x300 Hp**

**5 years warranty**

Come closer look...

There are a number of boating solutions waiting for you. Whether you prefer the elegance and relaxation of a lake, speed with open sea adventures or the thrill of powering from one island to another, Selva Marine will accompany you providing power, control and great service.

The wonderful world of powerboating is now affordable and ready. Reach inlets with your friends, enjoy a beautiful sunset with your partner, or amaze everyone with landscapes that will remain in their hearts together with a lifetime passion for the sea. This is the Selva Marine world, a constant surprise to enjoy. Join it now.



Selva Marine engines come with a five-year limited warranty. Certain conditions and exclusions apply including professional and commercial use.



**QuattroT**  
**XSX**

**12 MODELS**  
from 25HP to 2X300HP  
*IN 26 VERSIONS*

Burning acceleration and low consumption are the main characteristics of the Selva Marine 4-stroke range for leisure, professional or commercial use. So they are specially developed for the most demanding people. The advanced electronic system controls all the engine's functions in the best way and gives breath-taking performance and fuel economy.

p. 4



**QuattroT**

**33 MODELS**  
from 2,5HP to 2X300HP  
*in 103 VERSIONS*

This Selva Marine range has a strong and distinctive personality that operates in total respect of nature. The use of sophisticated technologies, their compactness, elegant and innovative design make these outboard motors a range that does not go unnoticed in the pleasure boating sector.

p. 10





**Amberjack**



**25XSR**

**Dorado E.F.I.**



**60XSR**

**Murena E.F.I.**



**70XSR**

**Spearfish E.F.I.**



**100XSR**



**115XS R**

## TECHNICAL CHARACTERISTICS

| Model   | AMBERJACK  | DORADO                           | MURENA                                     | SPEARFISH                        | SWORDFISH          |
|---|--|----------------------------------|--|----------------------------------|--------------------|
| Power (hp)  | <b>25 XSR EFI</b>  | <b>60 XSR EFI</b>                | <b>70 XSR EFI</b>                          | <b>100 XSR EFI</b>               | <b>115 XSR EFI</b> |
| Power (kW)  | 18,4   | 44,1                             | 51,5                                       | 73,6                             | 84,6               |
| Max. R.P.M.   | 5000 / 6000  |                                  | 5300/6300                                  | 5000/6000                        | 5300/6300          |
| Motor type  | 4 Stroke SOHC  |                                  | 4 Stroke SOHC - 16V<br>4 Stroke DOHC - 16V |                                  |                    |
| Swept volume c.c.   | 432  | 996                              |  | 1832                             |                    |
| Bore x Stroke (mm)  | 65 x 65.1  | 65x75                            |  | 81x88,9                          |                    |
| N° Cylinders  | 2 in-line  | 4 in-line                        |  |                                  |                    |
| Induction   | Electronic Injection   |                                  |  |                                  |                    |
| Choke   | Automatic  |                                  |  |                                  |                    |
| Fuel  | Petrol (for specifications see the user manual)  |                                  |  |                                  |                    |
| Fuel tank (L)   | Separate 23  |                                  |  | Not provided                     |                    |
| Lubrication   | Forced (oil sump)  |                                  |  |                                  |                    |
| Ignition  | C.D.I. Micro-computer  | T.C.I. / Computer                |  |                                  |                    |
| Ignition timing   | Electronic   |                                  |  |                                  |                    |
| Starting  | Manual or Electric   | Electric                         |  |                                  |                    |
| Alternator  | Standard 12V/190 W (regulator optional) on Manual start version<br>Standard 12V/190 W with regulator on Electric start version               | Standard 12V/200W with regulator |  | Standard 12V/420W with regulator |                    |
| Cooling   | Water cooled with pump-forced circulation  |                                  |  |                                  |                    |
| Exhaust   | Underwater through propeller   |                                  |  |                                  |                    |
| Steering system   | Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box according to version | Remote with remote control box   |  |                                  |                    |
| Type of remote control box provided (for the version with remote control box) | Single remote control box with safety switch   |                                  |  |                                  |                    |
| Trim adjustment   | Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version   | Power Trim/Tilt                  |  |                                  |                    |
| Gears   | Mechanical F-N-R   |                                  |  |                                  |                    |
| Transmission Ratio  | 13 / 27  | 13/24                            | 12/28                                      | 13/28                            |                    |
| Available shaft versions  | C. - L.  | L.                               | L.-XL.                                     |                                  |                    |
| Standard propeller type   | 3-bladed with built-in spring drive  |                                  |  |                                  |                    |
| Weight basic version (kg)   | 56   | 111                              | 119  | 162                              | 175                |

Some models may not be available in all countries or they may have different, non-standard horsepower depending on the different national legislative requirements. (For further details see the current price list.)

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights etc. without any forewarning or obligations.

**Killer Whale** E.F.I.



**150XSR**

**Sei Whale** E.F.I.



**200XSR**

**Right Whale** E.F.I.



**250XSR**



**300XSR**

## TECHNICAL CHARACTERISTICS

| Model   | KILLER WHALE                                    | SEI WHALE   | RIGHT WHALE                                | WHITE WHALE        |
|---|---|---|--|--------------------|
| Power (hp)  | <b>150 XSR EFI</b>                              | <b>200 XSR EFI</b>  | <b>250 XSR EFI</b>                         | <b>300 XSR EFI</b> |
| Power (kW)  | 110,3   | 147,1   | 183,9                                      | 220,7              |
| Max. R.P.M.   | 5000/6000                                       |   |  |                    |
| Motor type  | 4 Stroke DOHC - 16V                             | 4 Stroke DOHC - 16V at variable timing                          | 4 Stroke DOHC - 24V with VTC direct acting |                    |
| Swept volume c.c.   | 2670  | 2785  | 4169                                       |                    |
| Bore x Stroke (mm)  | 94x96,2   | 96 x 96,2   | 96 x 96                                    |                    |
| N° Cylinders  | 4 on line                                       |   | 6 a V 60°                                  |                    |
| Induction   | Electronic Injection                            |   |  |                    |
| Choke   | Automatic                                       |   |  |                    |
| Fuel  | Petrol (for specifications see the user manual) |   |  |                    |
| Fuel tank (L)   | Not provided                                    |   |  |                    |
| Lubrication   | Forced (oil sump)                               |   |  |                    |
| Ignition  | T.C.I./Computer                                 |   |  |                    |
| Ignition timing   | Electronic                                      |   |  |                    |
| Starting  | Electric  |   |  |                    |
| Alternator  | Standard 12V /420W with rectifier               | Standard 12V / 500W with rectifier                              | Standard 12V / 840W with rectifier         |                    |
| Cooling   | Water cooled with pump-forced circulation       |   |  |                    |
| Exhaust   | Underwater through propeller                    |   |  |                    |
| Steering system   | Remote with remote control box                  | Remote control box with <b>electronic control Drive By Wire</b> |  |                    |
| Type of remote control box provided (for the version with remote control box) | Single binnacle lever with safety switch        | Remote control box with electronic control Drive By Wire        |  |                    |
| Trim adjustment   | Power Trim/Tilt                                 |   |  |                    |
| Gears   | Mechanical F-N-R                                | Mechanical F-N-R electronic, operating Drive by Wire            |  |                    |
| Transmission Ratio  | 14/28   | 14/26   | 21/12                                      |                    |
| Available shaft versions  | L-XL.   | XL.   | XL.- UL.                                   |                    |
| Standard propeller type   | 3-bladed with built-in spring drive             |   |  |                    |
| Weight basic version (kg)   | 216   | 227   | 260  |                    |

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list). The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## COUNTER ROTATING PAIR

**Sei Whale** E.F.I.



**2x200XSR**

**Right Whale** E.F.I.



**2x250XSR**



# White Whale E.F.I.



**2x300XSR**

## TECHNICAL CHARACTERISTICS

| Model   | COUNTER ROTATING PAIR<br>SEI WHALE                                   | COUNTER ROTATING PAIR<br>RIGHT WHALE       | COUNTER ROTATING PAIR<br>WHITE WHALE |
|---|--|--|--------------------------------------|
| Power (hp)  | 2 x 200 XSR EFI  | 2 x 250 XSR EFI                            | 2 x 300 XSR EFI                      |
| Power (kW)  | 2 x 147,1  | 2 x 183,9                                  | 2 x 220,7                            |
| Max. R.P.M.   | 5000 / 6000  |  |                                      |
| Motor type  | 4 Stroke DOHC -<br>16V at variable timing                            | 4 Stroke DOHC - 24V with VTC direct acting |                                      |
| Swept volume c.c.   | 2 x 2785   | 2 x 4169                                   |                                      |
| Bore x Stroke (mm)  | 2 x 96 x 96,2  | 2 x 96 x 96                                |                                      |
| N° Cylinders  | 2 x 4 on line  | 2 x 6 a V 60°                              |                                      |
| Induction   | Electronic Injection   |  |                                      |
| Choke   | Automatic  |  |                                      |
| Fuel  | Petrol (for specifications see the user manual)                      |  |                                      |
| Fuel tank (L)   | Not provided   |  |                                      |
| Lubrication   | Forced (oil sump)  |  |                                      |
| Ignition  | T.C.I./Computer  |  |                                      |
| Ignition timing   | Electronic   |  |                                      |
| Starting  | Electric   |  |                                      |
| Alternator  | Standard 2 x 12V / 500W<br>with rectifier                            | Standard 2 x 12V / 840W with rectifier     |                                      |
| Cooling   | Water cooled with pump-forced circulation                            |  |                                      |
| Exhaust   | Underwater through propeller   |  |                                      |
| Steering system   | Remote control box with <b>electronic control Drive By Wire</b>      |  |                                      |
| Type of remote control box<br>provided (for the version with<br>remote control box) | Twin lever with electronic binnacle Drive by Wire with safety switch |  |                                      |
| Trim adjustment   | Power Trim/Tilt  |  |                                      |
| Gears   | Mechanical F-N-R electronic, operating Drive by Wire                 |  |                                      |
| Transmission Ratio  | 14/26  | 21/12                                      |                                      |
| Available shaft versions  | XL.  | XL. - UL.                                  |                                      |
| Standard propeller type   | 3-bladed with built-in spring drive                                  |  |                                      |
| Weight basic version (kg)   | 2 x 227  | 2 x 260                                    |                                      |

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).  
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

Guppy



2.5

Sea Bass



4/5

Sea Bass



6



6

## TECHNICAL CHARACTERISTICS

| Model                     | GUPPY   | SEA BASS  |     |     | OYSTER                           |
|---------------------------|---|---|-----|-----|----------------------------------|
| Power (hp)                | 2,5   | 4   | 5   | 6   | 6                                |
| Power (kW)                | 1,84  | 2,9   | 3,7 | 4,4 | 4,4                              |
| Max. R.P.M.               | 4500 / 5500   | 5000 / 5500   |     |     |                                  |
| Motor type                | 4 Stroke OHV  | 4 Stroke SOHC   |     |     |                                  |
| Swept volume c.c.         | 87  | 118   |     |     | 135                              |
| Bore x Stroke (mm)        | 54 x 38   | 56 x 48   |     |     | 57 x 53                          |
| N° Cylinders              | 1   |   |     |     |                                  |
| Induction                 | 1 carburettor   |   |     |     |                                  |
| Choke                     | Manual  |   |     |     |                                  |
| Fuel                      | Petrol (for specifications see the user manual)                                       |   |     |     |                                  |
| Fuel tank (L)             | Integrated 0.9  | Separate 12 or Integrated 1.6                             |     |     | Separate 12 or Integrated 1.8    |
| Lubrication               | Forced  | Automatic oil injection into fuel                         |     |     | Forced with mechanical lobe-pump |
| Ignition                  | C.D.I. Digital  |   |     |     |                                  |
| Ignition timing           | Electronic  |   |     |     |                                  |
| Starting                  | Manual  |   |     |     |                                  |
| Alternator                | Not available   | Optional 12V/70W with rectifier                           |     |     |                                  |
| Cooling                   | Water cooled with pump-forced circulation   |   |     |     |                                  |
| Exhaust                   | Underwater  | Underwater through propeller                              |     |     |                                  |
| Steering system           | Tiller bar steering with twist grip throttle control and steering friction adjustment |   |     |     |                                  |
| Trim adjustment           | Manual (4 pos)  | Manual (4 pos) with trim for navigation in shallow waters |     |     |                                  |
| Gears                     | Mechanical A-F + 360° shaft rotation  | Mechanical F-N-R + 360° shaft rotation                    |     |     |                                  |
| Transmission ratio        | 13 / 28   | 13 / 30   |     |     |                                  |
| Available shaft versions  | C.  | C.- L.  |     |     |                                  |
| Standard propeller type   | 3-bladed  | 3-bladed with built-in spring drive                       |     |     |                                  |
| Weight basic version (Kg) | 13,5  | 23  |     |     | 27                               |

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).  
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

**Oyster** B.F.



6

**Oyster** B.F. Sail



6

**Black Bass**



8





8

## TECHNICAL CHARACTERISTICS

| Model   | OYSTER BIG FOOT   | OYSTER BIG FOOT SAIL | BLACK BASS  | BLACK BASS BIG FOOT   |
|---|---|----------------------|---|---|
| Power (hp)  | 6   | 6                    | 8   | 8   |
| Power (kW)  | 4,4   | 4,4                  | 5,9   | 5,9   |
| Max. R.P.M.   | 5500 / 6000   |                      |   |   |
| Motor type  | 4 Stroke SOHC   |                      |   |   |
| Swept volume c.c.   | 135   |                      | 165   |   |
| Bore x Stroke (mm)  | 57 x 53   |                      | 63 x 53   |   |
| N° Cylinders  | 1   |                      |   |   |
| Induction   | 1 carburettor   |                      |   |   |
| Choke   | Manual or Electrical  |                      | Manual  | Manual or Electrical  |
| Fuel  | Petrol (for specifications see the user manual)   |                      |   |   |
| Fuel tank (L)   | Separate 12   |                      | Separate 12 or built-in 1.8   | Separate 12   |
| Lubrication   | Forced with mechanical lobe-pump  |                      |   |   |
| Ignition  | C.D.I. Digital  |                      |   |   |
| Ignition timing   | Electronic  |                      |   |   |
| Starting  | Manual or Electric also with integrated ISB battery (not available in versions with built-in tank)                      |                      |   |   |
| Alternator  | Optional 12V/70W with rectifier on Manual start version<br>Standard 12V/70W with rectifier on Electric start version    |                      |   |   |
| Cooling   | Water cooled with pump-forced circulation   |                      |   |   |
| Exhaust   | Underwater through propeller  |                      |   |   |
| Steering system   | Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box |                      | Tiller bar steering with twist grip throttle control and steering friction adjustment | Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box |
| Type of remote control box provided (for the version with remote control box) | Single lever with safety switch   |                      | Not applicable  | Single lever with safety switch   |
| Trim adjustment   | Manual (4 pos) with trim for navigation in shallow waters   |                      |   |   |
| Gears   | Mechanical F-N-R  |                      | Mechanical F-N-R + 360° shaft rotation  | Mechanical F-N-R  |
| Transmission Ratio  | 13 / 27   |                      | 13 / 30   | 13 / 27   |
| Available shaft versions  | C. - L.   | XL.                  | C. - L.   |   |
| Standard propeller type   | 3-bladed with built-in spring drive   |                      |   |   |
| Weight basic version (kg)   | 30,5  | 32                   | 27  | 30,5  |

Some models may not be available in all countries, or they may have different, non-standard horse powers.

Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

**Black Bass** *B.F. Sail*



8

**Ray**



8

**Piranha**



9.9



9.9

## TECHNICAL CHARACTERISTICS

| Model   | BLACK BASS<br>BIG FOOT SAIL   | RAY   | PIRANHA   | PIRANHA SAIL |
|---|---|---|---|--------------|
| Power (Hp)  | 8   | 8   | 9,9   | 9,9          |
| Power (kW)  | 5,9   | 5,9   | 7,3   | 7,3          |
| Max. R.P.M.   | 5500 / 6000   | 5000 / 6000   | 5500 / 6000   |              |
| Motor type  | 4 Stroke SOHC   |   |   |              |
| Swept volume c.c.   | 165   | 212   | 181   |              |
| Bore x Stroke (mm)  | 63 x 53   | 56 x 43   | 66 x 53   |              |
| N° Cylinders  | 1   | 2 in-line   | 1   |              |
| Induction   | 1 carburettor   |   |   |              |
| Choke   | Manual or Electrical  | Manual  | Manual or Electrical  |              |
| Fuel  | Petrol (for specifications see the user manual)   |   |   |              |
| Fuel tank (L)   | Separate 12   |   |   |              |
| Lubrication   | Forced with mechanical lobe-pump  | Forced (oil sump)   | Forced with mechanical lobe-pump  |              |
| Ignition  | C.D.I. digital  | C.D.I. Micro-computer   | C.D.I. digital  |              |
| Ignition timing   | Electronic  |   |   |              |
| Starting  | Manual or Electrical also with integrated ISB battery   | Manual  | Manual or Electrical also with integrated ISB battery                                 |              |
| Alternator  | Optional 12V/70W with rectifier on Manual start version<br>Standard 12V/70W with rectifier on Electric start version    | Standard 12V/70W (regulator optional)   | Optional 12V / 70W with regulator (A. M.)<br>Standard 12V / 70W with regulator (A.E.) |              |
| Cooling   | Water cooled with pump-forced circulation   |   |   |              |
| Exhaust   | Underwater through propeller  |   |   |              |
| Steering system   | Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box | Tiller bar steering with twist grip throttle control and steering friction adjustment | Tiller bar steering with twist grip throttle control and steering friction adjustment |              |
| Type of remote control box provided (for the version with remote control box) | Single lever with safety switch   | Accessory, Single lever   | Single lever with safety switch   |              |
| Trim adjustment   | Manual (4 pos) with trim for navigation in shallow waters   |   |   |              |
| Gears   | Mechanical F-N-R  |   |   |              |
| Transmission Ratio  | 13 / 27   |   |   |              |
| Available shaft versions  | XL.   | C- L.   |   | XL.          |
| Standard propeller type   | 3-bladed with built-in spring drive   |   |   |              |
| Weight basic version (kg)   | 32  | 39,9  | 30,5  | 32           |

Some models may not be available in all countries, or they may have different, non-standard horse powers.

Depending on the different national legislative requirements. (For further details consult the current price list).

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

**Pike**



**9.9**

**Wahoo**



**15**

**Wahoo**



**20**





25

## TECHNICAL CHARACTERISTICS

| Model   | PIKE   |   | WAHOO     |  | AMBERJACK   |
|---|--|---|-----------|--|---|
| Power (hp)  | 9,9  |   | 15        | 20   | 25 <b>EFI</b>   |
| Power (kW)  | 7,3  |   | 11        | 14,7   | 18,4  |
| Max. R.P.M.   | 5000 / 6000  |   |           |  |   |
| Motor type  | 4 Stroke SOHC  |   |           |  |   |
| Swept volume c.c.   | 212  |   | 362       |  | 432   |
| Bore x Stroke (mm)  | 56 x 43  |   | 63 x 58,1 |  | 65 x 65.1   |
| N° Cylinders  | 2 in-line  |   |           |  |   |
| Induction   | 1 carburettor  |   |           |  | Electronic Injection  |
| Choke   | Manual   |   | Automatic |  |   |
| Fuel  | Petrol (for specifications see the user manual)  |   |           |  |   |
| Fuel tank (L)   | Separate 12  |   |           | Separate 23  |   |
| Lubrication   | Forced (oil sump)  |   |           |  |   |
| Ignition  | C.D.I. Micro-computer  |   |           |  |   |
| Ignition timing   | Electronic   |   |           |  |   |
| Starting  | Manual or Electric   |   |           |  |   |
| Alternator  | Standard 12V/70W (regulator optional) on Manual start version Standard 12V/70W with regulator on Electric start version                      | Standard 12V/120W (regulator optional) on Manual start version Standard 12V/120W with regulator on Electric start version |           |  | Standard 12V/190W (regulator optional) on Manual start version Standard 12V/190W with regulator on Electric start version |
| Cooling   | Water cooled with pump-forced circulation  |   |           |  |   |
| Exhaust   | Underwater through propeller   |   |           |  |   |
| Steering system   | Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box according to version |   |           |  |   |
| Type of remote control box provided (for the version with remote control box) | Single lever with safety switch  |   |           |  |   |
| Trim adjustment   | Manual (4 pos) with trim for navigation in shallow waters  |   |           | Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version | Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version                          |
| Gears   | Mechanical F-N-R   |   |           |  |   |
| Transmission Ratio  | 13 / 27  |   |           |  |   |
| Available shaft versions  | C. - L.  |   |           |  |   |
| Standard propeller type   | 3-bladed with built-in spring drive  |   |           |  |   |
| Weight basic version (kg)   | 39,9   |   | 51,7      |  | 56  |

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list). The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

**Aruana** E.F.I.



**40**

**Dorado** E.F.I.



**50**

**Dorado** E.F.I.



**60**


**70**

# TECHNICAL CHARACTERISTICS

| Model   | ARJANA  | DORADO                                       |        | MURENA              |
|---|---|--|--------|---------------------|
| Power (hp)  | 40 EFI  | 50 EFI                                       | 60 EFI | 70 EFI              |
| Power (kW)  | 29,4  | 36,8   | 44,1   | 51,5                |
| Max. R.P.M.   | 5000 - 6000   |  |        | 5300 - 6300         |
| Motor type  | 4 Stroke SOHC   |  |        | 4 Stroke SOHC - 16V |
| Swept volume c.c.   | 747   | 996  |        |                     |
| Bore x Stroke (mm)  | 65 x 75   |  |        |                     |
| N° Cylinders  | 3 in-line   | 4 in-line                                    |        |                     |
| Induction   | Electronic injection  |  |        |                     |
| Choke   | Automatic   |  |        |                     |
| Fuel  | Petrol (for specifications see the user manual)   |  |        |                     |
| Fuel tank (L)   | Separate 23   |  |        |                     |
| Lubrication   | Forced (oil sump)   |  |        |                     |
| Ignition  | T.C.I./Computer   |  |        |                     |
| Ignition timing   | Electronic  |  |        |                     |
| Starting  | Electric  |  |        |                     |
| Alternator  | Standard 12V/190W with regulator  | Standard 12V/200W with regulator             |        |                     |
| Cooling   | Water cooled with pump-forced circulation   |  |        |                     |
| Exhaust   | Underwater through propeller  |  |        |                     |
| Steering system   | Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box, depending on the version | Single remote control box with safety switch |        |                     |
| Type of remote control box provided (for the version with remote control box) | Single remote control box with safety switch  |  |        |                     |
| Trim adjustment   | Servo-assisted with Hydraulic shock absorber or Power Trim/Tilt depending on the version  | Power Trim/Tilt                              |        |                     |
| Gears   | Mechanical F-N-R  |  |        |                     |
| Transmission Ratio  | 13 / 26   | 13 / 24                                      |        | 12 / 28             |
| Available shaft versions  | L.  |  |        | L-XL.               |
| Standard propeller type   | 3-bladed with built-in spring drive   |  |        |                     |
| Weight basic version (kg)   | 99  | 111  |        | 119                 |

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).  
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

**Spearfish** E.F.I.



**80xs/100**

**Swordfish** E.F.I.



**115**

**Killer Whale** E.F.I.



**150**





200

## TECHNICAL CHARACTERISTICS

| Model   | SPEARFISH                                       |         | SWORDFISH           | KILLER WHALE                             | SEI WHALE  |
|---|---|---------|---------------------|--|--|
| Power (hp)  | 80 XS EFI                                       | 100 EFI | 115 EFI             | 150 EFI                                  | 200 EFI  |
| Power (kW)  | 58,8  | 73,6    | 84,6                | 110,3                                    | 147,1  |
| Max. R.P.M.   | 5000 / 6000                                     |         | 5300 / 6300         | 5000 / 6000                              |  |
| Motor type  | 4 Stroke SOHC - 16V                             |         | 4 Stroke DOHC - 16V |  | 4 Stroke DOHC - 16V at variable timing   |
| Swept volume c.c.   | 1832  |         |                     | 2670                                     | 2785   |
| Bore x Stroke (mm)  | 81 x 88,9                                       |         |                     | 94x96,2                                  | 96 x 96,2  |
| N° Cylinders  | 4 in-line                                       |         |                     |  |  |
| Induction   | Electronic Injection                            |         |                     |  |  |
| Choke   | Automatic                                       |         |                     |  |  |
| Fuel  | Petrol (for specifications see the user manual) |         |                     |  |  |
| Fuel tank (L)   | Not provided                                    |         |                     |  |  |
| Lubrication   | Forced (oil sump)                               |         |                     |  |  |
| Ignition  | T.C.I./Computer                                 |         |                     |  |  |
| Ignition timing   | Electronic                                      |         |                     |  |  |
| Starting  | Electric  |         |                     |  |  |
| Alternator  | Standard 12V/420W with regulator                |         |                     |  | Standard 12V/500W with regulator   |
| Cooling   | Water cooled with pump-forced circulation       |         |                     |  |  |
| Exhaust   | Underwater through propeller                    |         |                     |  |  |
| Steering system   | Remote with remote control box                  |         |                     |  | Remote control box with electronic control Drive By Wire<br>Single lever with electronic binnacle Drive by Wire with safety switch |
| Type of remote control box provided (for the version with remote control box) | Single remote control box with safety switch    |         |                     | Single binnacle lever with safety switch |  |
| Trim adjustment   | Power Trim/Tilt                                 |         |                     |  |  |
| Gears   | Mechanical F-N-R                                |         |                     |  | Mechanical F-N-R electronic, operating Drive by Wire   |
| Transmission Ratio  | 13/28   |         |                     | 14/28                                    | 14/26  |
| Available shaft versions  | L - XL  |         |                     |  | XL   |
| Standard propeller type   | 3-bladed with built-in spring drive             |         |                     |  |  |
| Weight basic version (kg)   | 162   |         | 175                 | 216                                      | 227  |

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).  
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

**Beaked Whale** E.F.I.



**225**

**Right Whale** E.F.I.



**250**



**300**

## TECHNICAL CHARACTERISTICS

| Model   | BEAKED WHALE   | RIGHT WHALE | WHITE WHALE |
|---|--|-------------|-------------|
| Power (hp)  | 225 EFI  | 250 EFI     | 300 EFI     |
| Power (kW)  | 165,5  | 183,9       | 220,7       |
| Max. R.P.M.   | 5000/6000  |             |             |
| Motor type  | 4 Stroke DOHC - 24V with VTC direct acting                             |             |             |
| Swept volume c.c.   | 4169   |             |             |
| Bore x Stroke (mm)  | 96 x 96  |             |             |
| N° Cylinders  | 6 a V 60°  |             |             |
| Induction   | Electronic Injection   |             |             |
| Choke   | Automatic  |             |             |
| Fuel  | Petrol (for specifications see the user manual)                        |             |             |
| Fuel tank (L)   | Not provided   |             |             |
| Lubrication   | Forced (oil sump)  |             |             |
| Ignition  | T.C.I. / Computer  |             |             |
| Ignition timing   | Electronic   |             |             |
| Starting  | Electric   |             |             |
| Alternator  | Standard 12V / 840W with regulator                                     |             |             |
| Cooling   | Water cooled with pump-forced circulation                              |             |             |
| Exhaust   | Underwater through propeller   |             |             |
| Steering system   | Remote control box with <b>electronic control Drive By Wire</b>        |             |             |
| Type of remote control box provided (for the version with remote control box) | Single lever with electronic binnacle Drive by Wire with safety switch |             |             |
| Trim adjustment   | Power Trim/Tilt  |             |             |
| Gears   | Mechanical F-N-R ,electronic, operating Drive by Wire                  |             |             |
| Transmission Ratio  | 21/12  |             |             |
| Available shaft versions  | XL.  | XL. - UL.   |             |
| Standard propeller type   | 3-bladed with built-in spring drive                                    |             |             |
| Weight basic version (kg)   | 260  |             |             |

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list). The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## COUNTER ROTATING PAIR

**Sei Whale** E.F.I.



COUNTER ROTATING PAIR  
**2x200**

**Beaked Whale** E.F.I.  
**Right Whale** E.F.I.



COUNTER ROTATING PAIR  
**2x225/250**





COUNTER ROTATING PAIR  
**2x300**

## TECHNICAL CHARACTERISTICS

| Model   | COUNTER ROTATING PAIR<br>SEI WHALE                                   | COUNTER ROTATING PAIR<br>BEAKED WHALE      | COUNTER ROTATING PAIR<br>RIGHT WHALE | COUNTER ROTATING PAIR<br>WHITE WHALE |
|---|--|--|--------------------------------------|--------------------------------------|
| Power (hp)  | 2 x 200 EFI  | 2 x 225 EFI                                | 2 x 250 EFI                          | 2 x 300 EFI                          |
| Power (kW)  | 2 x 147,1  | 2 x 165,5                                  | 2 x 183,9                            | 2 x 220,7                            |
| Max. R.P.M.   | 5000 / 6000  |  |                                      |                                      |
| Motor type  | 4-Stroke DOHC - 16V at variable timing                               | 4 Stroke DOHC - 24V with VTC direct acting |                                      |                                      |
| Swept volume c.c.   | 2 x 2785   | 2 x 4169                                   |                                      |                                      |
| Bore x Stroke (mm)  | 2 x 96 x 96,2  | 2 x 96 x 96                                |                                      |                                      |
| N° Cylinders  | 2 x 4 in linea   | 2 x 6 a V 60°                              |                                      |                                      |
| Induction   | Electronic Injection   |  |                                      |                                      |
| Choke   | Automatic  |  |                                      |                                      |
| Fuel  | Petrol (for specifications see the user manual)                      |  |                                      |                                      |
| Fuel tank (L)   | Not provided   |  |                                      |                                      |
| Lubrication   | Forced (oil sump)  |  |                                      |                                      |
| Ignition  | T.C.I. / Computer  |  |                                      |                                      |
| Ignition timing   | Electronic   |  |                                      |                                      |
| Starting  | Electric   |  |                                      |                                      |
| Alternator  | Standard 12V/500W with regulator                                     | Standard 2 x 12V/840W with regulator       |                                      |                                      |
| Cooling   | Water cooled with pump-forced circulation                            |  |                                      |                                      |
| Exhaust   | Underwater through propeller   |  |                                      |                                      |
| Steering system   | Remote control box with electronic control Drive By Wire             |  |                                      |                                      |
| Type of remote control box provided (for the version with remote control box) | Twin lever with electronic binnacle Drive by Wire with safety switch |  |                                      |                                      |
| Trim adjustment   | Power Trim/Tilt  |  |                                      |                                      |
| Gears   | Mechanical F-N-R electronic, operating Drive by Wire                 |  |                                      |                                      |
| Transmission Ratio  | 14/26  | 21/12                                      |                                      |                                      |
| Available shaft versions  | XL.  |  | XL. - UL.                            |                                      |
| Standard propeller type   | 3-bladed with built-in spring drive, counter rotating pair           |  |                                      |                                      |
| Weight basic version (kg)   | 2 x 227  | 2 x 260                                    |                                      |                                      |

Some models may not be available in all countries, or they may have different, non-standard horse powers.  
Depending on the different national legislative requirements. (For further details see the current price list).  
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## AVAILABLE ENGINES CONTROL

### Mechanical controls



### Drive by wire controls



### Digital screen



## AVAILABLE PROPELLERS



**GS aluminium series**  
for Aruana and Dorado



**KS aluminium series**  
for Murena, Spearfish and Swordfish



**KS Series Inox polished**  
for Spearfish and Swordfish



**MS Series Inox polished**  
for Killer Whale and Sei Whale



**TS Series Inox polished**  
for Beaked Whale, Right Whale and White Whale



**MXS Series in polished stainless steel**  
CNC precision machined  
for Killer Whale and Sei Whale



**TXS Series In polished stainless steel**  
CNC precision machined  
for Beaked Whale, Right Whale and White Whale



**MS4 Series Polished stainless steel 4-blade**  
for Killer Whale, Sei Whale, Beaked Whale, Right Whale and White Whale



**SELVA S.p.A.**

*Head office and main factory:*

*Viale dell'Industria, 13*

*23037 Tirano (SO) - Italia*

*Tel. 0342 702451 - Fax 0342 70536*

*VAT Number IT 00050830140*

*Company Registration SO n. 00050830140*

*REA n. 18382*

**www.selvamarine.com**



**Q8 Oils**